


DELIA T2 - PMMA

Dimensions:	ø 400 mm
Color:	white
Type:	ceiling mounted
Shade:	opal polymethylmetacrylate
Shade attach.:	two-step clamp holders
Pendant:	wire
Length of pendant:	L100 - 1000mm
Fixture:	powder coated steel sheet
Equipment:	STANDARD, LED



Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
Classic								
52057	IN-22ZT11/PM23/L100	IP40		2x30	2xE27		1,0	60

LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
Classic									
48379	LED-1L16B07ZT11/PM23/L100 3000	IP40	3000	36	4850	3400		2,0	60
48879	LED-1L16B07ZT11/PM23/L100 4000	IP40	4000	36	5070	3550		2,0	60
66323	LED-1L16C07ZT11/PM23/L100 3000	IP40	3000	28	3690	2580		1,0	60
66823	LED-1L16C07ZT11/PM23/L100 4000	IP40	4000	28	3890	2720		1,0	60
Dimmable									
48383	LED-1L16B07ZT11/PM23/L100 DALI 3000	IP40	3000	36	4850	3400		2,0	60
48883	LED-1L16B07ZT11/PM23/L100 DALI 4000	IP40	4000	36	5070	3550		2,0	60
66324	LED-1L16C07ZT11/PM23/L100 DALI 3000	IP40	3000	28	3690	2580		1,0	60
66824	LED-1L16C07ZT11/PM23/L100 DALI 4000	IP40	4000	28	3890	2720		1,0	60
Emergency combined									
48385	LED-1L16B07ZT11/PM23/NK1W/L100 3000	IP40	3000	36	4850	3400	3	2,0	24
48885	LED-1L16B07ZT11/PM23/NK1W/L100 4000	IP40	4000	36	5070	3550	3	2,0	24
66325	LED-1L16C07ZT11/PM23/L100/NK1W 3000	IP40	3000	28	3690	2580	3	1,0	24
66825	LED-1L16C07ZT11/PM23/L100/NK1W 4000	IP40	4000	28	3890	2720	3	1,0	24