


ALKOR 1,2,3



TECHNICAL DATA

Light source	LED module Osmont L09C, L10C, L11B	incandescent lamp
Chromacity temperature	3000K, 4000K	by source
CRI	3000K Ra>80, 4000K Ra>80	by source
Power source	Tridonic	-
Lifetime of LED	50 000 hod / L80B10 (ambient temperature 25°C)	by source
Energy class	A++	by source
Photobiological safety of lamps by EN 62471 (Blue light hazard)	safe (Risk group – 0)	by source
Input voltage	230V	
IP	IP44	
Ambient temperature	from -20°C to +30°C	
Warranty	5 years	
Fixture	metal	
Color of fixture	white	
Shade	three layers glass with matt surface	
Shade attachment	with folding holders	
Mounting	wall, ceiling	
Applications	housing constructions (rooms, corridors), cultural premises	

VARIANTS

LED:

	Type	Input [W]	Luminous flux LED [lm]		Luminous flux of luminaire [lm]	
			3000K	4000K	3000K	4000K
ALKOR 1	LED-1L09C03KN01/405.000	2	310	330	270	280
ALKOR 2	LED-1L10C03KN02/406.000	5	620	650	500	520
ALKOR 3	LED-1L11B07KN03/407.000	8	970	1010	780	800


.000 – 3000K or 4000K

STANDARD:

	Type	Input [W]	Socket
ALKOR 2	IN-12KN02/406	1x60	1xE27
ALKOR 3	IN-12KN03/407	1x60	1xE27

DIMENSIONS

DIMENSIONS OF LUMINAIRE [mm]:



	ØA1	A2
ALKOR 1	104	120
ALKOR 2	140	156
ALKOR 3	184	200

MOUNTING DIMENSIONS [mm]:

<p>ALKOR 1</p>	
<p>ALKOR 2</p>	
<p>ALKOR 3</p>	