


# ELEKTRA 4,5



## TECHNICAL DATA

Light source	LED module Osmont L12C, L18C	incandescent lamp
Chromacity temperature	3000K, 4000K	by source
CRI	3000K Ra>80, 4000K Ra>80	by source
Lifetime of LED	50 000 hrs / L80B10 (ambient temperature 25°C)	by source
Power source	Tridonic	-
Photobiological safety of lamps by EN 62471 (Blue light hazard)	safe (Risk group – 0)	by source
Energy class	A++	by source
Input voltage	230V	
IP	IP65	
Ambient temperature	from -20°C to +30°C	
Shock resistance	IK10	
Warranty	5 years	
Fixture	polycarbonate	
Color	white	
Shade	transparent polycarbonate, opal polycarbonate (LED)	
Shade attachment	with screw	
Mounting	wall, ceiling	
Applications	industrial premises, outdoor premises	

## VARIANTS

LED:

	Type	Input [W]	Luminous flux LED [lm]		Luminous flux of luminaire [lm]		Possibility Sensor (HF)
			3000K	4000K	3000K	4000K	
ELEKTRA 4	LED-1L12C03/IN-172P.000	9	1080	1140	870	920	•
	LED-1L18C03/IN-172P.000	15	2000	2110	1620	1710	•

LED emergency combined:

	Type	Input [W]	Luminous flux LED [lm]		Luminous flux of luminaire [lm]		Luminous flux LED in emergency mode		T [hrs]	Type of battery
			3000K	4000K	3000K	4000K	[%]	[lm]		
ELEKTRA 4	LED-1L12C03/IN-172P/NK1W.000	9	1080	1140	870	920	14	150	3	Ni-Cd (3,6V/1,6Ah)
	LED-1L18C03/IN-172P/NK1W.000	15	2000	2110	1620	1710	7	150	3	Ni-Cd (3,6V/1,6Ah)


.000 – 3000K or 4000K

STANDARD:

	Type	Input [W]	Socket	Possibility
				Sensor (HF)
ELEKTRA 4	IN-172	100	E27	• (1x60W)
ELEKTRA 5	IN-174	2x60	2xE27	•

## DIMENSIONS

DIMENSIONS OF LUMINAIRE [mm]:



	ØA1 [mm]	A2 [mm]
ELEKTRA 4	260	110
ELEKTRA 5	310	120

MOUNTING DIMENSIONS [mm]:

