


MIRA R



TECHNICAL DATA

Light source	LED module Osmont L06C	incandescent lamp
Chromacity temperature	3000K, 4000K	by source
CRI	3000K Ra>80, 4000K Ra>80	by source
Lifetime of LED	50 000 hod / L80B10 (ambient temperature 25°C)	by source
Power source	Tridonic	-
Photobiological safety of lamps by EN 62471 (Blue light hazard)	safe (Risk group – 0)	by source
Energy class	A++	by source
Input voltage	230V	
IP	IP 40	
Ambient temperature	from -20°C to +30°C	
Warranty	5 years	
Pendant	chain	
Color	old bronze (SB), brass (MS)	
Shade	three layers glass with matt surface	
Shade holder	screw	
Mounting	ceiling	
Applications	office spaces	

Type	Lenght [mm]
r2	400
r3	600
r4	800
r5	1000

VARIANTS

LED:

Type	Input [W]	Luminous flux LED [lm]		Luminous flux of luminaire [lm]		Possibility DIM (DALI)
		3000K	4000K	3000	4000K	
LED-5L06C06Z11/195/r. x.000	29	3900	4110	3430	3620	•

STANDARD:

Type	Input [W]	Socket
Z11/195/r. x	150	E27

r. – pendant length
x – color (SB – old bronze, MS – brass)
.000 – 3000K or 4000K

DIMENSIONS

DIMENSIONS OF LUMINAIRE [mm]:

