


# NELA 4A



## TECHNICAL DATA

Light source	LED module Osmont L26B	incandescent lamp
Chromacity temperature	3000K, 4000K	by source
CRI	3000K Ra>80, 4000K Ra>80	by source
Lifetime of LED	50 000 hod / L80B10 (ambient temperature 25°C)	by source
Power source	Tridonic	-
Photobiological safety of lamps by EN 62471 (Blue light hazard)	safe (Risk group – 0)	by source
Energy class	A++	by source
Input voltage	230V	
IP	IP43	
Ambient temperature	from -20°C to +30°C	
Warranty	5 years	
Fixture	metal	
Color of fixture	white	
Shade	three layers glass with matt surface	
Shade attachment	with folding holders	
Mounting	wall	
Applications	housing constructions (rooms, corridors), cultural premises	

## VARIANTS

LED:

Type	Input [W]	Luminous flux LED [lm]		Luminous flux of luminaire [lm]	
		3000K	4000K	3000K	4000K
LED-1L26B07U31/322..000	8	970	1010	650	680


..000 – 3000K or 4000K

STANDARD:

Type	Input [W]	Socket
IN-12U31/322	100	E27

## DIMENSIONS

DIMENSIONS OF LUMINAIRE [mm]:



MOUNTING DIMENSIONS [mm]:

